



TBG 620

HIGH SPEED SHREDDER



AGGRESSIVE Shredding

Intelligent control and flexible deployment.

Shredding without destroying whilst making a new quality material.

Ideal for shredding of waste wood for making particle boards and for biomass. Green waste and branch wastes are optimally recycled for composting.

Terex Ecotec Benefits:

- Tested CAN bus control with automatic detection of overload
- Terex Ecotec material auto pilot for load dependent power input
- Extra-large feed chamber for efficient non-stop performance
- Motor control and automatic cleaning of the cooling unit (standard)
- Tested, roadworthy carrier with airbrake
- The 3.5 or 5.0 metre long discharging transport belt can be equipped with a magnetic separator.



EFFICIENCY GENERATING MONEY.





CAN bus control for an efficient and secure system management. Automatic detection of overload. All at one glance and quick response options.

Large feed chamber for constant material feeding. Ideal specifications for non-stop productivity under all circumstances.



Excellence service access reduces operator downtime Only short dwell times and a daily inspection in a couple of minutes

Highest level of efficiency Direct power transmission from motor through coupling to the flail bar

Reduced tool wear and tear The easily replaceable mallet is equipped with hard metal plates. Excellent service access reduces operator downtime.





Options which can increase the individual applications:

- 5 metre long conveyor belt
- Overband magnet on conveyor to capture iron and other metals
- · Fire fighting equipment

EFFICIENT SHREDDER FOR WOOD-WASTE AND GREEN-WASTE.

The TBG 620 is a robust and reliable shredder, with efficient deployment for wood waste and green waste applications.

ECOTEC

- Robust and time-tested technology for reliable and trouble-free functioning
- User friendly operation х.
- Intelligent control
- Excellent service points to reduce downtime

- TECHNICAL DATA Main Data

Main Data		
Concept	Robust and heavy shredder	
Weight	20,000 kg	
Width x Length x Height	2,550 x 9,850 x 3,700 mm	
Feed Intake Width	1,450 mm	
Tires	385 / 65 R 22,5	
Application area		
Suitable for chopping tough branch material, demolition and industrial timl	ber	
Performance		
Maximal capacity of chopped material	up to 175 m³/h	
Engine specifications		
Engine	Scania DC13	
Performance	500 HP / 368 kW	
Diesel tank	450	
Electrical system	24 Volt	
Emission Standards	Tier 4 Final	
Exhaust System	SCR AdBlue, without particulate filter	
Hydraulic system		
Oil tank capacity No. 1	150 l	
Oil tank capacity No. 2	50	
Hydraulic fan drive with reversible function		
Mallet		
Number of hammers	28	
Weight of each hammer	16 kg / pc	
Rotor speed	1,200 rpm	
Driven via PT Tech clutch and two 4-band belts		
Feed chamber		
Length x Breadth x Depth	3,500 x 1,530 x 850 mm	
Load intake height / Load intake length / width	2,250 mm / 5,000 mm / 1,960 mm	
Rear conveyor belt short (3.5m)		
Length / Belt width	3,500 mm / 1,800 mm	
Max. Loading height with a belt of 3.5 m	2,300 mm	
Rear conveyor belt long 5.0 m		
Length	5,000 mm	
Belt width	1,600 mm	
Maximal unloading height with a belt of 5 m	3,100 mm	

Main Data			
Concept	Robust and heavy shredder		
Neight	20,000 kg		
Vidth x Length x Height	2,550 x 9,850 x 3,700 mm 1,450 mm		
eed Intake Width			
ires	385 / 65 R 22,5	5 / 65 R 22,5	
Application area			
Suitable for chopping tough branch material, demolition and industrial	timber		
Performance			
Naximal capacity of chopped material	up to 175 m³/h		
Engine specifications			
ingine	Scania DC13		
Performance	500 HP / 368 kW		
Diesel tank	450 l		
Electrical system	24 Volt		
Emission Standards	Tier 4 Final		
xhaust System	SCR AdBlue, without particulate filter		
łydraulic system			
Dil tank capacity No. 1	150		
)il tank capacity No. 2	50 l		
Hydraulic fan drive with reversible function			
Vallet			
Number of hammers	28		
Veight of each hammer	16 kg / pc		
Rotor speed	1,200 rpm		
Priven via PT Tech clutch and two 4-band belts			
eed chamber			
ength x Breadth x Depth	3,500 x 1,530 x 850 mm	3,500 x 1,530 x 850 mm	
oad intake height / Load intake length / width	2,250 mm / 5,000 mm / 1,960 mm		
Rear conveyor belt short (3.5m)			
ength / Belt width	3,500 mm / 1,800 mm		
/lax. Loading height with a belt of 3.5 m	2,300 mm		
Rear conveyor belt long 5.0 m			
an adh	5,000 mm		
ength			
Length Belt width	1,600 mm		

Number of hammers	
Weight of each hammer	
Rotor speed	
Driven via PT Tech clutch and two 4-band belts	

Subject to change without notice

only available on 5m discharge conveyor | Central lubrication

BUSE



TBG 620

CUSTOMER SUPPORT With you every step of the way

We work with our customers to understand their equipment needs so to select the product most suited to their business requirements. Terex Ecotec customer support incorporates a range of services including parts, technical support, warranty and financial services.

Ō The Right Part at the Right Time

Terex Ecotec has a full inventory of genuine Terex parts through our global support locations and dealer network. We are committed to getting the right parts delivered at the right time. Using genuine Terex parts ensures optimum performance and reliability.

Expert technical support

Terex Ecotec provide highly qualified service personnel to ensure that we have Terex Ecotec are able to offer finance solutions to our customers. Our team of finance professionals know the importance of working closely with customers to the ability to provide technical support when our customers need it. This support understand their unique business challenges as well as their financial goals and is provided in conjunction with our dealer network. We ensure our customers are supported throughout the lifecycle of their machine. Terex works for you. requirements. Obtaining financing is often a time-consuming task, so we work hard to provide a reliable, flexible and responsive service.





Warrantv Delivering on our promise so you can keep yours

Terex Ecotec warrants its new equipment to be free of defects in material or manufacture for a specified period from the date the equipment is first used.

Terex Financial Services Financing that works for you.



DUNGANNON

32 Farlough Road Dungannon, Co. Tyrone BT71 4DT, Northern Ireland

Tel: +44 (0) 28 87 718 500

NEWTON

Dealer Stamp:

22 Whittier Street Newton, New Hampshire USA, 03858

Tel: +1 (603) 382 0556

January 2018. The material in this document is for information only and is subject to change without notice. Terex Ecotec assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein. Due to continual product development we reserve the right to change specifications without notice. Any product performance figures given in this brochure are for guidance purposes only. This information does not constitute an expressed or implied warranty or guarantee, but shows text examples provided. These results will vary depending on product settings, screen media and sizes, feed source and types of material being processed. Photographs are for illustrative purposes only. Some or all of the machines in the illustrativons may be fitted with optional extra. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or its subsidiaries in the USA and other countries. All rights reserved. Terex is a registered trademark of Terex Corporation in the USA and many other countries @ 2018 Terex Corporation.

