

PRODUCT  
SPECIFICATION

 **TEREX**®

 **ECOTEC**

# TTS 620

TROMMEL



# THE ULTIMATE IN TROMMEL DESIGN

Terex Ecotec's TTS 620 is the ultimate in modern trommel design, offering operators unrivalled application flexibility, production rates and serviceability. A highly efficient engine and hydraulic drive system combined with advanced material processing control system offer maximum production combined with minimum costs. It is ideally suited for screening compost, biomass, soil, gravel & waste.



# TTS 620

Unprecedented levels of service access catapults the TTS 620 into a league of its own.



An intuitive push button control panel allows the operator to easily configure the machine to suit the required application while the intelligent feeder control system continually adjusts the feeder speed to optimize screening rates. Special consideration has been given to minimize change out time for the screening drum. The process, which takes a matter of minutes, places the TTS 620 as a market leader. The machine has also been designed to accept a number of other manufacturers screening drums allowing customers to smoothly integrate the TTS 620 into established fleets.

Unprecedented levels of service access catapults the TTS 620 into a league of its own. All conveyors are built to a modular design allowing each one to be removed independently for ease of maintenance. The swing out engine cradle gives operators

unrestricted ground level access to all service components. Hinged doors on both sides of the trommel drum offers unobstructed access for maintenance and cleaning.

The machine has been designed to run at a low engine RPM, reducing fuel usage, emissions and noise levels. Both Tier III and Tier IV options are available with the Tier III being a constant speed configuration making it suitable for use within Europe.

Due to ever changing market conditions and demands of the modern trommel the machine will be available in wheeled, pintle drawbar, or tracked configurations.

# KEY FEATURES



Double sided unrestricted drum access via two large swing out doors allows for easy maintenance and cleaning



Easily replaced 5.5m (18') x 2m (6'7") punch plate drum which is compatible with the Doppstadt SM620 and Neuenhauser 6020



Advanced feeder control system offering efficient operation and maximised output

Fully sealed feeder reducing spillage

The feeder belt is driven at the head drum via a powerful recessed gearbox and hydraulic motor reducing belt slippage



Swing out engine cradle giving operators unrivalled levels of maintenance access



All conveyors are built to an individual modular design to reduce maintenance downtime

Advanced sealing and feedboot design ensures smooth material transfer and stockpiling

Removable pre filter grill provides maximum protection for the engine air intake and cooling radiator







### DUNGANNON

32 Farlough Road  
Dungannon, Co. Tyrone  
BT71 4DT, Northern Ireland

Tel: +44 (0) 28 87 718 500

### NEWTON

22 Whittier Street  
Newton, New Hampshire  
USA, 03858

Tel: +1 (603) 382 0556

---

Dealer Stamp:

---

February 2019. The material in this document is for information only and is subject to change without notice. TEE assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein. Due to continual product development we reserve the right to change specifications without notice. Any product performance figures given in this brochure are for guidance purposes only. This information does not constitute an expressed or implied warranty or guarantee, but shows text examples provided. These results will vary depending on product settings, screen media and sizes, feed source and types of material being processed. Photographs are for illustrative purposes only. Some or all of the machines in the illustrations may be fitted with optional extra. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or its subsidiaries in the USA and other countries. All rights reserved. Terex is a registered trademark of Terex Corporation in the USA and many other countries © 2019 Terex Corporation.